



TELEPHONE CABLES

Finolex Telephone cables with high density polyethelene insulated, solid annealed high conductivity bare copper with DIA 0.5mm, paired, polyester taped and sheathed with high oxygen index Fire Retardent PVC compound, generally conforming to ITD specifications G / WIR-06/02. May 94 and Finolex specifications.

**Product Code	Type	LP per 90 Mtr Rs.	Packing
31050013	1 pair	525	Standard length of the coil is 90 Mtrs.
31050023	2 pair	905	
31050033	3 pair	1340	
31050043	4 pair	1755	
31050053	5 pair	2180	
31050103	10 pair	4225	
31050203	20 pair	7895	
31050503	50 pair	19095	Standard length of the drum is 500m +/-10%
31051001	100 pair	37130	

Finolex Telephone cables with high density polyethelene insulated, solid annealed high conductivity bare copper with DIA 0.4 mm, paired, polyester taped and sheathed with high oxygen index Fire Retardent PVC compound, generally conforming to ITD specifications G / WIR-06/02. May 94 and Finolex specifications.

**Product Code	Type	LP per 90 Mtr Rs.	Packing
31040013	1 pair	395	Standard length of the coil is 90 Mtrs.
31040023	2 pair	655	
31040033	3 pair	965	
31040043	4 pair	1205	
31040053	5 pair	1480	
31040103	10 pair	2975	
31040203	20 pair	5455	
31040503	50 pair	13085	Standard length of the drum is 500m +/-10%
31041001	100 pair	24625	

A nylon ripcord is provided for slitting the jacket without damaging the insulated cores. The outersheath colour is Grey. For any other pairage please refer to Marketing Department.

NOTES :	
	The items marked as * are Non-Stock items. Please refer to Marketing Department for delivery confirmation indicating quantity, packing length, colour etc.
1. PRICES	GST extra as applicable.
2. PACKING	Available in 90 M coils for 1P to 20P Cables. 50 P cables available in 500m +/-10%
3. PRINTING	Cables are printed with Company Name, Logo, Type .
4. ALTERATION	This Price List supersedes all our earlier price lists and is subject to change without notice.

