



POLYCAB INDIA LIMITED

LDC LP No. 08/2018-19 Dtd : 1st March 2019

List of Products Covered in Our LDC LP

Coaxial Cables

Lan Cables

Telephone Switchboard Cables

Telephone Dry Armoured Cables

Submersible Cables

Single Core Flexible Cables

Multicore Flexible Cables

Single Core XLPE Unarmoured/Armoured Cables

CCTV Cables

Fire Alarm Cables

Solar Cables

BMS Cables

Braided Cables

Steel Braided Cables

Speaker Cables

Welding Cables

Aluminium Service Wires

Instrumentation Cables

Rubber Cables

JFTC Unarmoured/Armoured Cables

RS 485 Cables

Fire Survival Cables

Festoon Cables

Uninyvin Cables

Optical Fibre Cables

FS Aluminium Cables



POLYCAB INDIA LIMITED

LDC LP No. 08/2018-19 Dtd : 1st March 2019

POLYCAB INDUSTRIAL JELLY FLOODED COAXIAL CABLES

Polycab Gas Injected Physical Polyethylene Foam Insulation with Laminated Aluminium Tape and Aluminium Wire Braid, Jelly Flooded PVC Black Jacketed Industrial Coaxial Cables.

Size	100m Unarmoured	305m Unarmoured	1000m Flexible Armoured
RG - 59	1800	5495	78500
RG - 6	2280	6955	85500
RG - 11	5000	15245	121000
RG-6 CCS	1625	4965	75000
RG-11 CCS	3345	10200	111000

POLYCAB LAN (COMPUTER) CABLES

Polycab 4 Pair Unshielded Twisted Pair (UTP) LAN (Computer) Cables

Polycab 4 Pair Shielded Twisted Pair (STP) LAN (Computer) Cables

	Unarmoured - Rate per 305 m	Flexible Armoured- Rate per 1000m	Unarmoured - Rate per 305 m	Flexible Armoured- Rate per 1000m
CAT 5 E	8165	87000	10100	99000
CAT 6	8920	98000	11350	108000



POLYCAB INDIA LIMITED

LDC LP No. 08/2018-19 Dtd : 1st March 2019

POLYCAB INDUSTRIAL TELEPHONE (SWITCHBOARD) CABLES					POLYCAB IND. 3C FLAT SUBMERSIBLE CABLES	
<p>Polycab High Conductivity Solid Annealed Bare Copper industrial Telephone (Switchboard) Cables with High Density Polyethylene Insulation, Paired, Polyester and Sheathed with High Oxygen Index, Fire Retardant, PVC Compound, Grey Outer Sheath generally conforming ITD Specification</p>					<p>Polycab PVC Insulated and PVC Sheathed Industrial 3 Core Flat Submersible Cable with Bare Bunched Copper Conductor for Submersible Pump Motors with Voltage Grade 1100 Volts as per IS:694/2010</p>	
					Nominal Area of Conductor (sq mm)	Rate per 100m (Rs)
					1.5	6810
					2.5	11000
					4	16000
<p>Polycab Special PVC Insulated & PVC Sheathed Industrial 3 Core Flat Submersible Cables with Bare Bunched Copper Conductor for Submersible Pump Motors with Voltage Grade 1100 Volts generally conforming to IS 694/2010</p>						
					Nominal Area of Conductor (sq mm)	Rate per 100m (Rs)
					6	24800
					10	42400
					16	69900
					25	111600
					35	156500
					50	224100
					70	312100
					95	402900
					120	515000
					150	641700
					Notes :	
					2) Polycab Three Core Flat Submersible Cables	
					Insulated & Sheathed with XLPE can be supplied at	
					the same rates as given above.	
					Page 2 of 25	

POLYCAB INDUSTRIAL TELEPHONE (SWITCHBOARD) CABLES					
No. of Pairs & Size	Rate / 100 Mtr. (Rs.)		Rate / 90 Mtr (Rs.)		Master Packing
	0.4 mm	0.5 mm	0.4 mm	0.5 mm	
1 Pair	630	765	565	690	20
2 Pair	1075	1320	970	1190	20
3 Pair	1445	1955	1300	1760	16
4 Pair	1775	2555	1600	2300	12
5 Pair	2225	3195	2005	2875	8
10 Pair		6100		5490	1
20 Pair		12100		10890	1
50 Pair		34000			1
100 Pair		65300			1

ARMOURED TELEPHONE CABLES		
No. of Pairs	Rate / 100m (0.5mm)	Master Packing
2 Pair	6650	Drums/Coils as required
5 Pair	10500	Drums/Coils as required
10 Pair	15300	Drums/Coils as required
20 Pair	19500	Drums/Coils as required
50 Pair	45900	Drums/Coils as required
100 Pair	90800	Drums/Coils as required



POLYCAB INDIA LIMITED

LDC LP No. 08/2018-19 Dtd : 1st March 2019

Polycab FR Insulated Single Core Unsheathed Industrial Flexible Cable conforming to IS 694:2010 with Flexible Bright Annealed Copper Conductor for Voltage Grade 1100 Volts

Polycab PVC Insulated and PVC Round Sheathed Multi Core Bright Annealed Bare Copper Conductor Heavy Duty Industrial Cables for Voltage Grade 1100 Volts as per IS: 694:2010

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	(Rate/100m)		(Rate/100m)					
			Single Core	Packing	2 Core	3 Core	4 Core	2 - 4 Core Packing	5 Core	6 Core
0.5	16/.2	5	690	25	2035	2725	3505	4	4540	5425
0.75	24/.2	8	980	25	2710	3680	4580	4	6345	7770
1	32/.2	13	1275	20	3300	4505	5785	4	8365	9790
1.5	30/.25	17	1830	16	4415	6155	8095	4	11100	13500
2.5	50/.25	24	2995	12	7095	9940	12900	3	18100	21600
4	56/.3	30	4650	8	10800	15200	20000		27700	34700
6	84/.3	38	6760	6	15300	22300	29000		42500	51100
10	80/.4	52	11600	1	26800	38700	50200		72700	
16	126/.4	70	18700	1	43500	62700	82700		115700	
25	196/.4	88	30300	1	83300	113500	149100		194000	
35	276/.4	110	41500	1	114100	157300	206400		268200	
50	396/.4	145	59300	1	165100	224100	299700		388500	
70	354/.5	215	82400	1	235300	322200	418600		542000	
95	484/.5	260	113500	1	317500	441400	582800		748000	
120	608/.5	305	144800	1	401700	560200	751400		971300	
150	750/.5	355	181200	1	501700	695700	918700		1189700	
185	925/.5	415	225400	1	618300	845100	1120300		1452000	
240	1210/.5	500	290200	1	802600	1115300	1474000		1913200	
300	1527/.5	585	365800	1	1002900	1390600	1843600		2379200	
400	2036/.5	695	492500	1	1337300	1831100	2426900		3156200	



POLYCAB INDIA LIMITED

LDC LP No. 08/2018-19 Dtd : 1st March 2019

Polycab PVC Insulated, PVC Round Sheathed Multi Core Industrial Flexible Cable conforming to IS 694:2010 with Flexible Bright Annealed Copper Conductor for Voltage Grade 1100 Volts

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Rate Per 100 Mtrs. Coil			
			7 Core	8 Core	10 Core	12 Core
0.5	16/.2	5	6200	7300	9000	10700
0.75	24/.2	8	8400	10400	12500	14900
1	32/.2	13	11200	13000	15800	18800
1.5	30/.25	17	15100	17800	21900	26300
2.5	50/.25	24	24600	28700	35700	42500
4	56/.3	30	44900	51300	65100	79800
6	84/0.3	37	59600			

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Rate Per 100 Mtrs. Coil			
			14 Core	16 Core	19 Core	24 Core
0.5	16/.2	5	12400	13900	16200	20800
0.75	24/.2	8	17300	19800	23300	29400
1	32/.2	13	22100	25000	30000	37700
1.5	30/.25	17	30500	34300	40800	51400
2.5	50/.25	24	49400	56600	66200	83000

Polycab Multi Strand Bare Copper conductor XLPE insulated PVC Sheathed Cables					CCTV Cables (Rate/90m)	
Nominal Area	No/Dia of Strands	Current rating in Air at 40°C	Cu Conductor Unarmoured Cables	Cu Conductor Aluminium Armouring Cables	CCTV Cables 4+1	CCTV Cables 3+1
mm ²	No/mm		Rs/100 Mtr.	Rs/100 Mtr.	3675	3340
6	84/0.3	55	8900	12200	CCTV Armoured Cables (Rate/Km.)	
10	80/0.4	75	14800	20700	CCTV 4+1 Armoured	107000
16	126/0.4	103	22100	25900		
25	196/0.4	126	35000	39700		
35	276/0.4	152	47900	53200	Fire Alarm System Arm Cables (Rate/Mtr.)	
50	396/0.4	189	67000	74000	2 c x 1 Sq.mm. (Red)	90
70	354/0.5	240	92500	101800	2 c x 1.5 Sq.mm. (Red)	104
95	484/0.5	297	125000	130600		
120	608/0.5	346	158400	165300		
150	750/0.5	390	197800	206600		
185	925/0.5	460	241300	248900		
240	1210/0.5	552	313500	328400		
300	1527/0.5	640	390900	413000		
400	2036/0.5	753	521400	547300		



POLYCAB INDIA LIMITED

LDC LP No. 08/2018-19 Dtd : 1st March 2019

Polycab FRLS Insulated Single Core Unsheathed Industrial Flexible Cable conforming to IS 694:2010 with Flexible Bright Annealed Copper Conductor for Voltage Grade 1100 Volts

Polycab PVC Insulated and FRLS Round Sheathed Multi Core Bright Annealed Bare Copper Conductor Heavy Duty Industrial Cables for Voltage Grade 1100 Volts as per IS: 694:2010

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	Current Carrying Capacity (Amps)	Single Core (Rate/100m)	(Rate/100m)		
				Two Core	Three Core	Four Core
0.5	16/.2	5	740	2165	3010	3835
0.75	24/.2	8	1035	2920	4030	5220
1	32/.2	13	1345	3580	4985	6510
1.5	30/.25	17	1925	4745	6660	8975
2.5	50/.25	24	3200	7610	10800	14100
4	56/.3	30	5020	11700	16900	22100
6	84/.3	38	7110	17300	24400	32500
10	80/.4	52	12400	29100	42400	55900
16	126/.4	70	20100	47500	68700	90700
25	196/.4	88	31900	91600	126700	166400
35	276/.4	110	44200	124600	175500	229900
50	396/.4	145	62900	180800	249300	334100
70	354/.5	215	87400	257400	358800	466600
95	484/.5	260	120600	349000	485500	641000
120	608/.5	305	153900	442000	616100	826400
150	750/.5	355	192400	551300	765200	1010600
185	925/.5	415	239500	680200	929700	1232400
240	1210/.5	500	307600	882800	1226900	1621200
300	1527/.5	585	388500	1103300	1529700	2028100
400	2036/.5	695	522800	1471000	2014200	2669500



POLYCAP INDIA LIMITED

LDC LP No. 08/2018-19 Dtd : 1st March 2019

POLYCAP SOLAR WIRES / CABLES

Flexible Tinned Copper Conductor/ Cross linkable (E Beam) LSZH Insulation/ Cross linkable (E Beam) LSZH Sheathed Solar Cable as per EN 50618		Flexible Tinned Copper Conductor Single Core Multistrand, Cross Linked, Zero Halogen Low Smoke Insulation and Cross Linked Low Smoke Sheathing , Heat Resistant upto 120°C and UV Resistant Solar Cables		Flexible Bare Copper Conductor Multistrand XLPE / PVC Insulated and UV Stabalized PVC Sheathed Single Core Solar Cables	
Size in Sq.mm.	Rate Per 100m	Size in Sq.mm.	Rate Per 100m	Size in Sq.mm.	Rate Per 100m
2.5	4945	2.5	4400	2.5	3980
4	6765	4	6275	4	5895
6	9625	6	8920	6	8485
10	15900	10	15100	10	14400
16	24800	16	23000	16	22100
25	38300	25	36900		
35	52700	35	50600		
50	75000	50	71900		
70	107500	70	102600		
95	129300	95	121600		
120	163100	120	153600		
150	203700	150	191400		
185	251700	185	236800		
240	326400	240	307100		
300	408100	300	384200		

POLYCAP BUILDING MANAGEMENT SYSTEM CABLE (BMS)

Flexible Bare Copper Conductor, PVC Insulated, Cross Laid Up, Overall Aluminium Mylar Tape Shielded along with ATC Drain Wire PVC Outer Sheath BMS Cables (Rate/100m)

Cores	0.5 sq.mm (16/.2)	0.75 sq.mm (24/.2)	1.0 sq.mm (32/.2)	1.5 sq.mm (30/.25)	2.5 sq.mm (50/.25)
2	4500	5600	6400	7900	11300
3	5700	7000	8300	10300	15500
4	6900	8900	10300	13300	20100
5	8300	10300	12400	16100	24400
6	9500	12100	14800	19100	29200
7	10300	13600	16600	21200	32700
8	11600	15500	18900	24200	37400
10	14100	18800	22800	30200	46500
12	16600	21900	27100	35300	55000
14	18800	25300	31100	40900	63400
16	21200	28500	34500	46500	72700
19	24800	33500	41100	54600	84600
24	30700	42200	51500	66600	105600

Note : 3% Extra Charges for Drum Packing



POLYCAB INDIA LIMITED

LDC LP No. 08/2018-19 Dtd : 1st March 2019

POLYCAB INDUSTRIAL BRAIDED CABLES

Polycab Annealed Bare Cu Flexible Conductor PVC Insulated, Tinned Cu Braided (Screened) PVC Sheathed Flexible Unarmoured Cables 1100 Volts. (Rate per 100 Mtr)

Cores	0.5 sq.mm (16/.2)	0.75 sq.mm (24/.2)	1.0 sq.mm (32/.2)	1.5 sq.mm (30/.25)	2.5 sq.mm (50/.25)	4 sq.mm. (56/.3)	6 sq mm (84/.3)	10 sq.mm	16 sq.mm	25 sq mm	35 sq.mm.	50 sq.mm.
2	6600	7700	8600	10900	16000	23200	32300	62400	103900			
3	7700	9300	9900	13900	19800	30600	37500	78200	122400	164900	228800	299300
4	9300	11300	12800	17400	26800	37500	54500	111800	178700	239100	303100	431000
5	11000	15300	17200	21400	31000							
6	12800	16600	18800	24800	37200							
7	13700	18000	20100	26700	43000							
8	16300	21100	23700	30500	48700							
10	19600	25800	30400	38500	56700							
12	22100	29100	35900	45100	63100							
14	24300	33000	41200	52800	73300							
16	28100	36500	52400	57900	84400							
19	32000	42800	57700	68900	115900							
24	39900	50900	63500	84900	141200							



POLYCAB INDIA LIMITED

LDC LP No. 08/2018-19 Dtd : 1st March 2019

POLYCAB MULTICORE STEEL BRAIDED CABLES (Rate / 100 M)

Flex Bare Copper Conductor,PVC Insulated, Cores Laid Up Together PVC Inner Sheathed, GI Wire Braided (Flexible Armouring), Overall PVC Sheathed Steel Braided Cables.

Nominal Area of Conductor (sq mm)	Number/ Nom. Dia of Conductor (No./dia mm)	2 Core	3 Core	4 Core	Core	1.5 sq.mm (30/.25)	2.5 sq.mm (50/.25)
0.5	16/.2	6000	7200	8600	5	18100	27700
0.75	24/.2	7200	9000	10800	6	20800	32400
1	32/.2	8400	10600	13000	7	23200	36300
1.5	30/.25	9800	13000	16700	8	26500	41500
2.5	50/.25	14500	19600	24800	10	32400	51400
4	56/.3	21100	28100	36800	12	37800	60400
6	84/.3	29600	40400	52000	14	43600	69300
10	80/.4	43500	60300	80100	16	49200	78800
16	126/.4	65800	92100	120800	19	57500	92100
25	196/.4	99300	141200	186400	21	63400	101600
35	276/.4	136600	194000	255600	24	72100	115800
50	396/.4	191600	274500	362900			
70	354/.5	288200	414600	549700			
95	484/.5	388500	560300	744600			
120	608/.5	483800	699400	929200			
150	750/.5	603700	873400	1159600			
185	925/.5	751200	1076600	1428100			
240	1210/.5	960900	1393800	1852400			
300	1527/.5	1198900	1740700	2315500			

Note : 3% Extra Charges for Drum Packing

POLYCAB INDUSTRIAL SPEAKER WIRES

Speaker Wires (Oxygen Free) (Rate per 90 mtr)

Size	Price Per 90 Mtr.	Size	Price Per 90 Mtr.	Size	Price Per 90 Mtr.	Size	Price Per 90 Mtr.
23/36	1735	23/38	1225	0.5 Sq.mm	1670	1.5 Sq.mm	4385
40/36	2730	40/38	2040	0.75 Sq.mm	2395	2 Sq.mm	6135
70/36	4775	70/38	3205	1 Sq.mm	3025	2.5 Sq.mm	7165

** Flame Retardant, Heat Resistant up to 90°C & Oil Resistant

POLYCAB INDUSTRIAL WELDING CABLES

Polycab Flexible Copper Conductor 1100 Volts Welding Cable

Nominal Area of Conductor (sq mm)	Current Carrying Capacity	Conductor Constn. Strands/ Dia in mm	HOFr Insulation Rate/100m (Rs)
16	120	509/0.2	25800
25	160	796/0.2	37000
35	230	1115/0.2	50300
50	400	703/0.3	71200
70	600	999/0.3	101500
95	700	1346/0.3	134100
120	1100	1699/0.3	171800



POLYCAB INDIA LIMITED

LDC LP No. 08/2018-19 Dtd : 1st March 2019

POLYCAB ALUMINIUM WIRES & CABLES

POLYCAB <u>SINGLE CORE</u> PVC INSULATED 1100 VOLTS <u>SOLID</u> ALUMINIUM CONDUCTOR WIRES AS PER IS 694		POLYCAB <u>SINGLE CORE</u> PVC INSULATED 1100 VOLTS <u>STRANDED</u> ALUMINIUM CONDUCTOR WIRES AS PER IS 694		POLYCAB PVC INSULATED AND SHEATHED <u>TWIN CORE</u> & <u>THREE CORE</u> FLAT CABLES 1100 VOLTS EACH CORE HAVING SINGLE <u>STRANDED</u> ALUMINIUM CONDUCTOR SERVICE CABLES AS PER IS 694		
SQ.MM	RATE/ 100M	SQ.MM	RATE/ 100M	NO.OF CORES	SQ.MM	RATE/ 100M
1.5	435	1.5	445	2	1.5	1610
2.5	670	2.5	680	2	2.5	2280
4	880	4	920	2	4	3220
6	1340	6	1380	2	6	4210
10	1990	10	2070	2	10	6530
POLYCAB <u>SINGLE CORE</u> PVC INSULATED & <u>SHEATHED</u> 1100 VOLTS <u>STRANDED</u> ALUMINIUM CONDUCTOR WIRES AS PER IS 694		16	2980	2	16	8650
		25	4635	2	25	12300
		35	6250	2	35	15700
		50	8400	2	50	19900
SQ.MM	RATE/ 100M	70	11200	2	70	11200
1.5	660	95	13100	3	1.5	2200
2.5	815	120	19000	3	2.5	3300
4	1550	150	23600	3	4	4500
6	2110	185	29300	3	6	6400
10	2890	240	38100	3	10	9300
16	4110	300	47500	3	16	12700
25	5985	400	61000	3	25	17700
35	7630	500	77600	3	35	23100
50	10100	630	98300	3	50	29300
POLYCAB PVC INSULATED AND SHEATHED <u>TWIN CORE</u> & <u>THREE CORE</u> FLAT CABLES 1100 VOLTS EACH CORE HAVING SINGLE <u>SOLID</u> ALUMINIUM CONDUCTOR SERVICE CABLES AS PER IS 694				POLYCAB <u>XLPE</u> INSULATED AND PVC <u>SHEATHED</u> CABLE WITH EACH CORE HAVING <u>STRANDED</u> ALUMINIUM CONDUCTOR SERVICE CABLES GENERALLY CONFORMING TO IS 694.		
NO.OF CORES	SQ.MM		RATE/ 100M	NO.OF CORES	SQ.MM	RATE/100M
2	1.5		1495	2	4	2980
2	2.5		2185	2	6	4230
2	4		2980	2	10	5255
2	6		4135	2	16	7655
2	10		6350			
3	1.5		2070			
3	2.5		3220			
3	4		4665			
3	6		5900			
3	10		9060			



POLYCAB INDIA LIMITED

LDC LP No. 08/2018-19 Dtd : 1st March 2019

POLYCAB INSTRUMENTATION CABLES

**Str/Solid Cu PVC/XLPE Insulated Core/Pair/Triad/Quad laid up together with Al (Inner sheathed GI Steel Wire Mylar/Drain Wire)
Round/Strip Armoured PVC Outer Sheathed Instrumentation**

OVERALL SHIELDED - ARMURED INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr								
CORE	2	0.5	83	0.75	95	1	105	1.5	125	2.5	169
CORE	3	0.5	95	0.75	111	1	126	1.5	157	2.5	214
CORE	4	0.5	110	0.75	129	1	151	1.5	190	2.5	265
CORE	5	0.5	122	0.75	147	1	174	1.5	221	2.5	314
CORE	6	0.5	138	0.75	167	1	199	1.5	255	2.5	366
CORE	7	0.5	146	0.75	180	1	216	1.5	279	2.5	405
CORE	8	0.5	164	0.75	202	1	243	1.5	317	2.5	458
CORE	10	0.5	192	0.75	239	1	291	1.5	381	2.5	559
CORE	12	0.5	213	0.75	268	1	330	1.5	438	2.5	628
CORE	14	0.5	236	0.75	302	1	371	1.5	497	2.5	727
CORE	16	0.5	260	0.75	335	1	417	1.5	559	2.5	815
CORE	19	0.5	294	0.75	381	1	476	1.5	644	2.5	950
CORE	24	0.5	356	0.75	467	1	568	1.5	782	2.5	1184
PAIR	1	0.5	82	0.75	93	1	102	1.5	123	2.5	167
PAIR	2	0.5	121	0.75	144	1	162	1.5	203	2.5	288
PAIR	3	0.5	144	0.75	176	1	204	1.5	262	2.5	380
PAIR	4	0.5	169	0.75	212	1	250	1.5	324	2.5	477
PAIR	5	0.5	196	0.75	249	1	295	1.5	389	2.5	569
PAIR	6	0.5	223	0.75	287	1	341	1.5	453	2.5	667
PAIR	7	0.5	243	0.75	314	1	378	1.5	506	2.5	754
PAIR	8	0.5	273	0.75	355	1	429	1.5	566	2.5	854
PAIR	10	0.5	326	0.75	416	1	510	1.5	686	2.5	1050
PAIR	12	0.5	367	0.75	481	1	593	1.5	803	2.5	1231
PAIR	14	0.5	396	0.75	541	1	670	1.5	920	2.5	1415
PAIR	16	0.5	450	0.75	607	1	755	1.5	1030	2.5	1605
PAIR	19	0.5	509	0.75	703	1	876	1.5	1202	2.5	1877
PAIR	24	0.5	635	0.75	877	1	1086	1.5	1509	2.5	2357
TRIAD	1	0.5	98	0.75	116	1	125	1.5	156	2.5	218
TRIAD	2	0.5	153	0.75	189	1	212	1.5	272	2.5	394
TRIAD	3	0.5	189	0.75	240	1	274	1.5	360	2.5	533
TRIAD	4	0.5	226	0.75	293	1	342	1.5	453	2.5	670
TRIAD	5	0.5	263	0.75	349	1	407	1.5	547	2.5	814
TRIAD	6	0.5	304	0.75	404	1	475	1.5	631	2.5	959
TRIAD	7	0.5	334	0.75	448	1	532	1.5	713	2.5	1090
TRIAD	8	0.5	376	0.75	492	1	596	1.5	809	2.5	1245
TRIAD	10	0.5	447	0.75	609	1	723	1.5	995	2.5	1534
TRIAD	12	0.5	508	0.75	700	1	846	1.5	1161	2.5	1815
TRIAD	14	0.5	577	0.75	800	1	970	1.5	1335	2.5	2091
TRIAD	16	0.5	640	0.75	893	1	1087	1.5	1511	2.5	2372
TRIAD	19	0.5	740	0.75	1037	1	1268	1.5	1767	2.5	2781
TRIAD	24	0.5	915	0.75	1296	1	1586	1.5	2224	2.5	3501
QUAD	1	0.5	110	0.75	132	1	149	1.5	189	2.5	269



POLYCAB INDIA LIMITED

LDC LP No. 08/2018-19 Dtd : 1st March 2019

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad/Quad laid up together with Al Inner sheathed Mylar/Drain Wire PVC Inner Sheathed Unarmoured PVC Outer Sheathed Instrumentation Cable.

OVERALL SHIELDED - UNARMOURED INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr								
PAIR	1	0.5	48	0.75	58	1	69	1.5	81	2.5	114
PAIR	2	0.5	75	0.75	93	1	114	1.5	159	2.5	217
PAIR	3	0.5	98	0.75	125	1	159	1.5	206	2.5	309
PAIR	4	0.5	114	0.75	159	1	206	1.5	263	2.5	400
PAIR	5	0.5	149	0.75	195	1	287	1.5	319	2.5	493
PAIR	6	0.5	171	0.75	217	1	309	1.5	389	2.5	582
PAIR	7	0.5	184	0.75	251	1	319	1.5	432	2.5	673
PAIR	8	0.5	206	0.75	275	1	377	1.5	493	2.5	765
PAIR	10	0.5	251	0.75	355	1	457	1.5	617	2.5	959
PAIR	12	0.5	299	0.75	410	1	538	1.5	731	2.5	1130
PAIR	14	0.5	330	0.75	469	1	617	1.5	834	2.5	1302
PAIR	16	0.5	389	0.75	524	1	708	1.5	959	2.5	1483
PAIR	19	0.5	446	0.75	626	1	821	1.5	1119	2.5	1746
PAIR	24	0.5	549	0.75	776	1	1026	1.5	1405	2.5	2213
TRIAD	1	0.5	64	0.75	72	1	90	1.5	112	2.5	164
TRIAD	2	0.5	106	0.75	128	1	160	1.5	207	2.5	308
TRIAD	3	0.5	140	0.75	172	1	218	1.5	287	2.5	434
TRIAD	4	0.5	173	0.75	216	1	279	1.5	368	2.5	566
TRIAD	5	0.5	209	0.75	261	1	341	1.5	453	2.5	705
TRIAD	6	0.5	244	0.75	309	1	402	1.5	538	2.5	835
TRIAD	7	0.5	275	0.75	349	1	458	1.5	615	2.5	960
TRIAD	8	0.5	313	0.75	399	1	522	1.5	708	2.5	1094
TRIAD	10	0.5	383	0.75	491	1	653	1.5	876	2.5	1360
TRIAD	12	0.5	446	0.75	582	1	767	1.5	1036	2.5	1614
TRIAD	14	0.5	510	0.75	668	1	885	1.5	1196	2.5	1869
TRIAD	16	0.5	583	0.75	758	1	1004	1.5	1360	2.5	2136
TRIAD	19	0.5	680	0.75	886	1	1178	1.5	1598	2.5	2519
TRIAD	24	0.5	850	0.75	1112	1	1477	1.5	2023	2.5	3171
QUAD	1	0.5	69	0.75	85	1	110	1.5	149	2.5	217

**POLYCAB INDIA LIMITED**

LDC LP No. 08/2018-19 Dtd : 1st March 2019

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad laid up together with Al Mylar/Drain Wire Inner sheathed, GI Steel Wire Round/Strip Armoured PVC Outer Sheathed Instrumentation Cables

INDIVIDUAL & OVERALL SHIELDED - ARMoured INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr								
PAIR	2	0.5	159	0.75	174	1	200	1.5	244	2.5	334
PAIR	3	0.5	196	0.75	219	1	255	1.5	316	2.5	443
PAIR	4	0.5	234	0.75	267	1	313	1.5	394	2.5	548
PAIR	5	0.5	273	0.75	315	1	373	1.5	458	2.5	661
PAIR	6	0.5	314	0.75	365	1	432	1.5	542	2.5	775
PAIR	7	0.5	345	0.75	404	1	481	1.5	608	2.5	876
PAIR	8	0.5	392	0.75	446	1	538	1.5	689	2.5	1000
PAIR	10	0.5	463	0.75	545	1	657	1.5	844	2.5	1227
PAIR	12	0.5	526	0.75	625	1	758	1.5	986	2.5	1446
PAIR	14	0.5	600	0.75	713	1	867	1.5	1123	2.5	1661
PAIR	16	0.5	672	0.75	802	1	976	1.5	1267	2.5	1879
PAIR	19	0.5	769	0.75	922	1	1128	1.5	1478	2.5	2196
PAIR	24	0.5	959	0.75	1158	1	1416	1.5	1865	2.5	2762
TRIAD	2	0.5	187	0.75	217	1	245	1.5	306	2.5	419
TRIAD	3	0.5	234	0.75	277	1	320	1.5	406	2.5	574
TRIAD	4	0.5	285	0.75	343	1	397	1.5	497	2.5	730
TRIAD	5	0.5	335	0.75	407	1	476	1.5	607	2.5	895
TRIAD	6	0.5	388	0.75	463	1	547	1.5	712	2.5	1052
TRIAD	7	0.5	428	0.75	517	1	614	1.5	805	2.5	1195
TRIAD	8	0.5	478	0.75	593	1	696	1.5	920	2.5	1363
TRIAD	10	0.5	575	0.75	717	1	854	1.5	1129	2.5	1694
TRIAD	12	0.5	666	0.75	834	1	998	1.5	1318	2.5	1986
TRIAD	14	0.5	752	0.75	947	1	1144	1.5	1521	2.5	2287
TRIAD	16	0.5	845	0.75	1067	1	1283	1.5	1720	2.5	2595
TRIAD	19	0.5	979	0.75	1241	1	1507	1.5	2022	2.5	3041
TRIAD	24	0.5	1227	0.75	1561	1	1900	1.5	2527	2.5	3849



POLYCAB INDIA LIMITED

LDC LP No. 08/2018-19 Dtd : 1st March 2019

POLYCAB INSTRUMENTATION CABLES

Str/Solid Cu PVC/XLPE Insulated Pair/Triad laid up together with Al Mylar/Drain Wire Inner sheathed Unarmoured PVC Outer Sheathed Instrumentation Cable.

INDIVIDUAL & OVERALL SHIELED - UNARMoured INSTRUMENTATION CABLES

Type	No.	Size	Rate / mtr								
PAIR	2	0.5	98	0.75	114	1	139	1.5	171	2.5	241
PAIR	3	0.5	125	0.75	159	1	195	1.5	241	2.5	344
PAIR	4	0.5	159	0.75	195	1	241	1.5	309	2.5	446
PAIR	5	0.5	195	0.75	241	1	299	1.5	377	2.5	549
PAIR	6	0.5	228	0.75	287	1	355	1.5	446	2.5	653
PAIR	7	0.5	263	0.75	319	1	400	1.5	503	2.5	743
PAIR	8	0.5	299	0.75	364	1	457	1.5	582	2.5	857
PAIR	10	0.5	364	0.75	457	1	571	1.5	720	2.5	1050
PAIR	12	0.5	423	0.75	538	1	662	1.5	843	2.5	1256
PAIR	14	0.5	503	0.75	617	1	776	1.5	981	2.5	1450
PAIR	16	0.5	560	0.75	697	1	868	1.5	1119	2.5	1654
PAIR	19	0.5	653	0.75	821	1	1026	1.5	1312	2.5	1953
PAIR	24	0.5	821	0.75	1026	1	1291	1.5	1654	2.5	2454
TRIAD	2	0.5	135	0.75	152	1	186	1.5	234	2.5	337
TRIAD	3	0.5	180	0.75	209	1	257	1.5	325	2.5	477
TRIAD	4	0.5	226	0.75	267	1	330	1.5	422	2.5	626
TRIAD	5	0.5	275	0.75	322	1	402	1.5	516	2.5	771
TRIAD	6	0.5	320	0.75	381	1	476	1.5	619	2.5	915
TRIAD	7	0.5	362	0.75	432	1	545	1.5	708	2.5	1052
TRIAD	8	0.5	412	0.75	501	1	626	1.5	808	2.5	1201
TRIAD	10	0.5	516	0.75	616	1	773	1.5	1000	2.5	1502
TRIAD	12	0.5	604	0.75	724	1	912	1.5	1180	2.5	1781
TRIAD	14	0.5	694	0.75	834	1	1052	1.5	1365	2.5	2061
TRIAD	16	0.5	782	0.75	945	1	1194	1.5	1551	2.5	2343
TRIAD	19	0.5	915	0.75	1108	1	1404	1.5	1837	2.5	2742
TRIAD	24	0.5	1146	0.75	1401	1	1775	1.5	2309	2.5	3474



POLYCAB INDIA LIMITED

LDC LP No. 08/2018-19 Dtd : 1st March 2019

ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED, PCP OUTERSHEATHED ELASTOMERIC CABLE (Rate Per Mtr)

Cable Size in sq.mm	1 Core	2 Core	3 Core	4 Core	5 Core	6 Core	7 Core
4	101	253	328	415	578	673	745
6	152	373	489	639	815	924	1030
10	236	589	776	995	1287	1464	1639
16	345	845	1138	1467	1906	2156	2431
25	508	1313	1760	2284	2852	3519	3819
35	684	1721	2362	3036	3890	4603	5204
50	955	2409	3290	4238	5372	6472	7328
70	1294	3203	4398	5708			
95	1692	4228	5855	7592			
120	2110	5267	7289	9480			
150	2614	6485	9005	11724			
185	3205	7915	11032	14394			
240	4129	10138	14162	18489			
300	5097	12568	17579	22960			
400	6722	16469	23115	30254			
500	8363						
630	10373						

ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED, PCP OUTERSHEATHED ELASTOMERIC CABLE (Rate Per Mtr)

Number of Cores	1.5 Sq.mm.	2.5 Sq.mm.		Number of Cores	1.5 Sq.mm.	2.5 Sq.mm.
1	54	72		14	790	1095
2	140	191		16	881	1227
3	178	242		19	1011	1420
4	221	304		20	1073	1547
5	287	397		24	1294	1861
6	343	475		25	1333	1919
7	374	525		27	1419	2047
8	430	675		30	1581	2324
10	595	837		36	1950	2730
12	679	963		37	1981	2780



POLYCAB INDIA LIMITED

LDC LP No. 08/2018-19 Dtd : 1st March 2019

ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED, CSP OUTERSHEATHED ELASTOMERIC CABLE (Rate Per Mtr)

Cable Size in sq.mm	1 Core	2 Core	3 Core	4 Core	5 Core	6 Core	7 Core
4	119	321	394	486	688	789	860
6	184	478	596	772	420	500	598
10	279	745	934	1175	885	1020	1251
16	396	1038	1337	1693	1920	2250	2842
25	571	1606	2053	2607	3927	5265	6529
35	760	2064	2703	3412	7790	11180	13935
50	1050	2851	3726	4716	14643	20730	27041
70	1406	3724	4908	6275			
95	1824	4868	6487	8282			
120	2266	6032	8029	10297			
150	2795	7385	9872	12679			
185	3417	8979	12062	15540			
240	4371	11452	15426	19889			
300	5364	14158	19101	24640			
400	7046	18440	24986	32332			
500	8736						
630	10775						

ANNEALED TINNED COPPER CONDUCTOR , EPR INSULATED, CSP OUTERSHEATHED ELASTOMERIC CABLE (Rate Per Mtr)

Number of Cores	1.5 Sq.mm.	2.5 Sq.mm.		Number of Cores	1.5 Sq.mm.	2.5 Sq.mm.
1	70	89		14	962	1285
2	190	251		16	1063	1428
3	229	301		19	1203	1631
4	277	369		20	1275	1799
5	352	468		24	1549	2144
6	414	554		25	1588	2203
7	445	603		27	1680	2338
8	508	810		30	1852	2683
10	739	1011		36	2301	3118
12	829	1143		37	2332	3167



POLYCAB INDIA LIMITED

LDC LP No. 08/2018-19 Dtd : 1st March 2019

POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED, UNARMOURED POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION

Rate/Mtr.

SIZE	5 PAIR	10 PAIR	20 PAIR	50 PAIR	100 PAIR	200 PAIR
0.5	61	103	180	407	773	1514

POLYCAB BRAND JELLY FILLED TELEPHONE CABLES, SOLID ANNEALED COPPER, POLYTHENE INSULATED, PETROLEUM JELLY FILLED WITH POLY-AL LAMINATE MOISTURE BARRIER, POLYTHENE SHEATHED, G.S.TAPE ARMOURED POLYTHENE JACKETED TELEPHONE CABLES AS PER DOT/ POLYCAB SPECIFICATION

Rate/Mtr.

SIZE	5 PAIR	10 PAIR	20 PAIR	50 PAIR	100 PAIR	200 PAIR
0.5	110	162	248	503	895	1681

**POLYCAB INDIA LIMITED**

LDC LP No. 08/2018-19 Dtd : 1st March 2019

POLYCAB RS 485 CABLES (Armoured)500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / Extr. PVC ST1/ Armoured/ PVC ST1 sheathed Cable

Pairs	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	17 AWG	1.04	153
	18 AWG	0.82	145
	20 AWG	0.52	124
	22 AWG	0.33	119
	24 AWG	0.20	111
2 Pair	17 AWG	1.04	245
	18 AWG	0.82	231
	20 AWG	0.52	187
	22 AWG	0.33	175
	24 AWG	0.20	162

POLYCAB RS 485 CABLES (Un Armoured)500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / UnArmoured/ PVC ST1 sheathed Cable

Size	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	17 AWG	1.04	98
	18 AWG	0.82	91
	20 AWG	0.52	72
	22 AWG	0.33	67
	24 AWG	0.20	61
2 Pair	17 AWG	1.04	169
	18 AWG	0.82	154
	20 AWG	0.52	118
	22 AWG	0.33	107
	24 AWG	0.20	93

**POLYCAB INDIA LIMITED**

LDC LP No. 08/2018-19 Dtd : 1st March 2019

POLYCAB RS 485 CABLES (Armoured)500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / LSZH Extr. PVC ST1/ Armoured/ LSZH sheathed Cable

Pairs	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	17 AWG	1.04	172
	18 AWG	0.82	165
	20 AWG	0.52	143
	22 AWG	0.33	138
	24 AWG	0.20	130
2 Pair	17 AWG	1.04	272
	18 AWG	0.82	257
	20 AWG	0.52	211
	22 AWG	0.33	200
	24 AWG	0.20	186

POLYCAB RS 485 CABLES (Un Armoured)500 V, Str. Cu/ Polyethylene Ins/ Pairs Overall shielded with Al-mylar tape along with 0.5 mm² ATC Drain Wire & Tinned Annealed copper wire braid (80% Coverage) / UnArmoured/ LSZH sheathed Cable

Size	Size in Guage	Size in Sq.mm.	Rate/Mtr.
1 Pair	17 AWG	1.04	109
	18 AWG	0.82	101
	20 AWG	0.52	82
	22 AWG	0.33	76
	24 AWG	0.20	70
2 Pair	17 AWG	1.04	186
	18 AWG	0.82	171
	20 AWG	0.52	133
	22 AWG	0.33	122
	24 AWG	0.20	107



Fire Survival Cables

**Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Xlpe Insulation/Cores Laid up together/Fibre Glass Tape Wrapped/FRLS Inner Sheathed/GI Wire Strip Armoured/ FRLS Outersheathed
Fire Survival Cables**

					Rate/Mtr.
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores	
1.5	220	275		335	
2.5	275	351		433	
4	323	423		530	
6	418	560		709	
10	592	809		1035	
16	785	1095		1442	
25	1119	1612	1941	2118	
35	1488	2159	2496	2851	
50	1962	2868	3363	3797	
70	2727	4006	4687	5306	
95	3585	5277	6164	6994	
120	4460	6594	7857	8756	
150	5461	8086	9343	10730	
185	6746	10000	11707	13266	
240	8578	12741	14890	16919	
300	10626	15788	18424	20985	
400	13834	20580	23852	27356	



Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Xlpe Insulation/Cores Laid up together/Fibre Glass Tape Wrapped/Zero Halogen Inner Sheathed/GI Wire Strip Armoured/ Zero Halogen Outsheathed Fire Survival Cables

					Rate/Mtr.
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores	
1.5	247	303		366	
2.5	303	381		466	
4	352	453		563	
6	449	593		745	
10	627	846		1076	
16	818	1131		1487	
25	1161	1658	1992	2171	
35	1534	2210	2552	2910	
50	2013	2925	3425	3868	
70	2790	4079	4767	5391	
95	3656	5355	6251	7088	
120	4535	6680	7961	8868	
150	5551	8192	9461	10862	
185	6848	10125	11848	13420	
240	8700	12892	15060	17106	
300	10771	15963	18621	21209	
400	14014	20804	24104	27632	



Fire Survival Cables

Stranded Annealed Bare Copper Conductor /950° Mica Tape Wrapped/Cross Linkable Zero Halogen Insulation/Cores Laid up together/Fibre Glass Tape Wrapped/Zero Halogen Inner Sheathed/GI Wire Strip Armoured/ Zero Halogen Outersheathed Fire Survival Cables

Rate/Mtr.				
Size in Sq.mm.	2 Cores	3 Cores	3.5 Cores	4 Cores
1.5	256	317		383
2.5	313	396		486
4	362	469		584
6	461	611		769
10	641	867		1104
16	835	1156		1521
25	1188	1698	2040	2224
35	1564	2255	2605	2970
50	2052	2983	3496	3945
70	2840	4154	4857	5491
95	3711	5439	6353	7199
120	4603	6782	8087	9004
150	5639	8323	9617	11038
185	6960	10293	12043	13643
240	8834	13094	15296	17375
300	10929	16200	18903	21526
400	14212	21101	24458	28028



POLYCAB INDIA LIMITED

LDC LP No. 08/2018-19 Dtd : 1st March 2019

FESTOON CABLES

(Rate/Mtr.)

Cores	0.5	0.75	1	1.5	2.5	4	6	10	16	25	35
3	41	56	67	92	139	221	323	538	838	1329	1829
4	54	73	89	124	184	294	433	719	1120	1770	2436
5	70	95	117	159	237	380					
6	84	116	139	189	286	456					
7	96	134	160	220	331	530					
8	112	151	182	254	381	609					
9	128	177	212	290	439	693					
10	142	196	235	320	485	773					
12	169	232	279	382	578	923					
14	203	273	328	453	679	1083					
16	230	316	379	515	778	1241					
18	253	348	424	579	864	1380					
24	345	472	574	780	1163	1865					

**POLYCAB INDIA LIMITED**

LDC LP No. 08/2018-19 Dtd : 1st March 2019

UNINYVIN CABLES**Multistranded Annealed Tinned Copper Conductor 105° C PVC Insulation with Nylon Braiding with Lacquer Coating Uninyvin Cables**

Cable Size	Nom. Conductor Area (Sq.mm.)	Rate Per Mtr.
22	0.347	35
20	0.556	38
18	0.966	41
16	1.17	50
14	2.05	59
12	3.22	68
10	5.33	108
8	8.76	171
6	13.30	259
4	21.50	380
2	33.30	595
1	40.70	723
0	53.00	906
00	68.30	1161
000	84.20	1427
0000	109	1837



POLYCAB INDIA LIMITED

LDC LP No. 08/2018-19 Dtd : 1st March 2019

UNI-TUBE / MULTI-TUBE UN-ARMoured OPTICAL FIBRE CABLES

Cable Type	Fiber Type	Rate. Per Km.
2F MM-OM1 UNITUBE UNARMoured OFC WITH 2 FRP 6.0MM	Multimode	34241
4F MM-OM1 UNITUBE UNARMoured OFC WITH 2 FRP 6.0MM	Multimode	51253
6F MM-OM1 UNITUBE UNARMoured OFC WITH 2 FRP 6.0MM	Multimode	68288
12F MM-OM1 UNITUBE UNARMoured OFC WITH 2 FRP 6.5MM	Multimode	121439
24F MM-OM1 UNITUBE UNARMoured OFC WITH 2 FRP 7.0MM	Multimode	224255
24F MM-OM1 MULTITUBE UNARMoured OFC 9.8MM	Multimode	243855

UNI-TUBE / MULTI-TUBE ARMoured OPTICAL FIBRE CABLES

Cable Type	Fiber Type	Rate. Per Km.
2F MM-OM1 UNITUBE ARMoured OFC WITH 2 SW 8.0MM	Multimode	48716
4F MM-OM1 UNITUBE ARMoured OFC WITH 2 SW 8.0MM	Multimode	65766
6F MM-OM1 UNITUBE ARMoured OFC WITH 2 SW 8.0MM	Multimode	82815
12F MM-OM1 UNITUBE ARMoured OFC WITH 2 SW 8.0MM	Multimode	133964
24F MM-OM1 UNITUBE ARMoured OFC WITH 2 SW 8.5MM	Multimode	235882
24F MM-OM1 MULTITUBE ARMoured OFC 10.5MM	Multimode	253311



POLYCAB INDIA LIMITED

LDC LP No. 08/2018-19 Dtd : 1st March 2019

FS Aluminium Power Cables

Polycab Make Stranded Sector Aluminium Conductor/Wrapped with Mica Tape/Xlpe Insulation/Wrapped with Fibre Tape Barrier/FRLS Inner Sheathed/GI Wire Armoured/FRLS Sheathed FS Aluminium Power Cables

(Rate/Mtr.)

Sq.mm.	3 Core	4 Core
16	424	548
25	571	728
35	691	892
50	855	1109
70	1169	1521
95	1461	1901
120	1746	2288
150	2077	2721
185	2517	3288
240	3133	4097
300	3770	4949
400	4692	6146

• The above rates are exclusive of GST which shall be charged extra.